



writeINFINITY (dry erase paint)

Specifications

kit details

Small Kit:

- 50 sq. ft.
- 2 Roller Covers
- (one for Step 2 and one for Step 4 below)
- Installation Instructions
- Wet Paint Sign
- Paint Can Opener

Medium Kit:

- 100 sq. ft.
- 2 Roller Covers
- (one for Step 2 and one for Step 4 below)
- Installation Instructions
- Wet Paint Sign
- Paint Can Opener

Large Kit:

- 200 sq. ft.
- 2 Roller Covers
- (one for Step 2 and one for Step 4 below)
- Installation Instructions
- Wet Paint Sign
- Paint Can Opener

installation instructions summary

- Step 1.** Prime wall with water based paint primer (recommend the use of Zinsser 1-2-3 or Kilz Clean Start.)
- Step 2.** Paint wall with interior FLAT paint (recommend the use of Sherwin Williams Pro-Mar FLAT or equivalent) - install this step using provided L5 roller cover.
- Step 3.** Inspect surface for any unwanted texture. If present, lightly sand surface to ensure it is as smooth as possible.
- Step 4.** Install writeup1 using provided L5 roller cover (note: do not mix, shake or stir) using 2-3 wet mils maximum and working the product as necessary for a smooth even installation. Inspect from all angles to ensure no holes.
- Step 5.** Wait 10 minutes and back roll surface using only weight of roller to eliminate any unwanted texture or trapped air.

Technical Test Results:

TEST	ASTM METHOD	RESULT
VOC	D3960	4g/l
Coverage		Small Kit: 50 sq. ft. Medium Kit: 100 sq. ft. Large Kit: 200 sq. ft.
Density	D1475	9.44 Lbs/Gal
Sag Resistance	D4400	<3 mils
Crack Resistance/ Elongation	D522	>32%
Gloss 60 degree	D523	85-90 @ 3mil coating
QUV/500 hours,	D4587	Visual Gloss Change - Minimal
UVA 340		Visual Color Change - NONE Other Detrimental Film Effects - NONE DE = 1.40
Flammability	E84	Flame Spread: 5 Smoke Developed: 0
Flashpoint	D92	>200 F
Scrub Resistance	D2486	>15 000 cycles
Washability	D3450	98.8%