



writeINFINITY (dry erase clear paint)

safety data sheet

product and company Identification

Chemical family: polyfunctional polyisocyanate

hazards identification

Emergency overview

CAUTION:

Danger of skin sensitization on repeated contact
Irritating to skin
Ensure adequate ventilation
Eye wash fountains and safety showers must be easily accessible
Avoid inhalation of mists/vapors
Wear Safety glasses with side-shields
Wear protective clothing
Avoid contact with the skin, eyes and clothing

SENSITIZER.

May cause sensitization by inhalation.

State of matter: liquid
Color: colorless
Odor: faint odor

potential health effects

Primary Routes of exposure:

Routes of entry include eye and skin contact, ingestion and inhalation.

Sensitization:

No pulmonary sensitization potential was observed in the guinea pig model either after intradermal or inhalative induction with polyisocyanate based on hexamethylene diisocyanate. No sensitization of the respiratory tract as shown in animal studies.

No pulmonary sensitization potential was observed in the guinea pig model either after intradermal or inhalative induction with polyisocyanate based on hexamethylene diisocyanate. No sensitization of the respiratory tract as shown in animal studies.

Chronic Toxicity:

Repeated dose toxicity: No data available concerning repeated dose toxicity.

Signs and symptoms of overexposure:

The most important known symptoms and effects are described in the labeling (see section 2) and /or in section 1.1. Further important symptoms and effects are so far not known.

writeINFINITY (dry erase clear paint)

safety data sheet

composition / information on ingredients

CAS Number:	Content (W/W):	Hazardous ingredients:
28182-81-2 822-06-0	$\geq 96.0 - \leq 99.0$ % $\geq 0.1 - \leq 3.0$ %	Hexamethylene, 1,6-diisocyanate -, homopolymer 1,6-hexamethylene diisocyanate

first-aid measures

General advice:

Immediately remove contaminated clothing.

If inhaled:

If difficulties occur after vapor/aerosol has been inhaled, remove to fresh air and seek medical attention.

If on skin:

Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.

If in eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:

Rinse mouth immediately and then drink plenty of water, seek medical attention.

Note to physician

Treatment: Inhale corticosteroid dose aerosol. Treat according to symptoms (decontamination, vital functions), no known specific antidote, administer corticosteroid dose aerosol to prevent pulmonary edema.

fire-fighting measures

Flash point:	> 392 F° (200 °C) (DIN 51758)
Autoignition:	> 392 F° (200 °C) (DIN 51794)

Suitable extinguishing media:

dry extinguishing media, foam

Hazards during fire-fighting:

Evolution of fumes/fog. The substances/groups of substances mentioned can be released in case of fire.

Protective equipment for fire-fighting:

Wear a self-contained breathing apparatus.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.



writeINFINITY (dry erase clear paint)

safety data sheet

accidental release measures

Personal precautions:

Use personal protective clothing.

Environmental precautions:

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Cleanup:

Correctly dispose of recovered product immediately.

For small amounts: Pick up with absorbent material (e.g. sand, sawdust, general-purpose binder). For large amounts: Pump off product.

handling and storage

Handling

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame.

Storage

General advice:

Keep container tightly closed and in a cool place.

Storage stability:

If moisture enters isocyanate containers, CO₂ forms and pressure builds up.



writeINFINITY (dry erase clear paint)

safety data sheet

exposure controls and personal protection

Components with workplace control parameters

1,6-hexamethylene diisocyanate ACGIH TWA value 0.005 ppm ;

Personal protective equipment

Respiratory protection:

Suitable respiratory protection for lower concentrations or short-term effect. A NIOSH-certified (or equivalent) organic vapor respirator is preferred for LONG TERM use for industrial applications.

Hand protection:

Manufacturer's directions for use should be observed because of great diversity of types., Chemical resistant protective gloves

Eye protection:

Safety glasses with side-shields.

General safety and hygiene measures:

Handle in accordance with good industrial hygiene and safety practice. Wearing of closed work clothing is required additionally to the stated personal protection equipment. Avoid inhalation of mists. Contact with eyes and skin must be avoided. Wash soiled clothing immediately.

physical and chemical properties

Form: liquid

Odor: faint odor

Color: colorless

pH value: Not Applicable

Melting Point: Not Determined

Boiling Point: Not Determined

Vapor Pressure: 0.0001 mbar 68° F (20 °C)

Density: 1.1 g/cm3 68° F (20 °C) (DIN 51757)

Relative Density: 1.10

Viscosity, dynamic: 0.7 Pa.s 68° F (20 °C) (DIN 53019)

Solubility in water: Reacts with water to liberate CO2 gas

VOC: < 5 grams per liter of coating (calculated)



writeINFINITY (dry erase clear paint)

safety data sheet

stability and reactivity

Substances to avoid:

amines, amine compounds

Hazardous reactions:

Reacts with alcohols. Reacts with amines. Reacts with substances which contain active hydrogen. Reacts with water, with formation of carbon dioxide. The formation of gaseous decomposition products builds up pressure in tightly closed containers.

Decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

No decomposition if used correctly.

toxicological information

Acute toxicity

Oral:

Type of value: LD50
Species: rat
Value: > 2,000 mg/kg

Irritation / corrosion

Skin:

Species: rabbit
Result: non-irritant
Method: OECD Guideline 404

Eye:

Species: rabbit
Result: non-irritant
Method: OECD Guideline 405

Sensitization:

Buehler test Species: guinea pig
Result: Non-sensitizing.
Guinea pig maximization test
Result: sensitizing
sensitizing effect in animal tests

Other Information:

The product has not been tested. The statement has been derived from products of a similar structure and composition.



writeINFINITY (dry erase clear paint)

safety data sheet

ecological information

Aquatic invertebrates

Acute:

OECD Guideline 202, part 1 static

Daphnia magna/EL50 (48 h): > 100 mg/l

Nominal concentration. The product may hydrolyze.

The test result may be partially due to degradation products.

Microorganisms

Toxicity to microorganisms:

OECD Guideline 209 activated sludge, domestic/EC20 (180 min): approx. 150 mg/l

The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations. Nominal concentration.

Degradability / Persistence

Biological / Abiological Degradation

Test method: OECD 301B; ISO 9439; 92/69/EEC, C.4-C, activated sludge

Method of analysis: CO₂ formation relative to the theoretical value

Degree of elimination: 20 - 30 % (28 d)

Evaluation: Poorly biodegradable.

Other adverse effects:

Do not release untreated into natural waters. The local regulations on waste-water treatment must be followed. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

disposal considerations

Waste disposal of substance:

Dispose of in a licensed facility. Do not discharge into waterways or sewer systems without proper authorization.

Container disposal:

Dispose of in a licensed facility. Recommend crushing, puncturing or other means to prevent unauthorized use of used containers.



writeINFINITY (dry erase clear paint)

safety data sheet

transport information

Land Transport

TDG Not classified as a dangerous good under transport regulations

Sea Transport

IMDG Not classified as a dangerous good under transport regulations

Air Transport

IATA/ICAO Not classified as a dangerous good under transport regulations

regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released w/o restriction on quantity
TSCA & SPMN approved

OSHA Hazard Category:

Hazardous

EPCRA 311/312 (Hazard Categories):

Acute

other information

HMIS Rating

Health 1

Flammability 1

Physical Hazard 0

0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe



writeINFINITY (dry erase clear paint)

safety data sheet

The method of hazard communication for is comprised of Product Labels and Material Safety Data Sheets. HMIS ratings are provided by as a customer service. The HMIS system was designed to communicate workplace hazard information to employees who handle hazardous chemicals.

The handling of products containing reactive HDI polyisocyanate/prepolymer and/or monomeric HDI requires appropriate protective measures referred to in this MSDS. These products are therefore recommended only for use in industrial or trade (commercial) applications. They are not suitable for use in Do-It-Yourself applications.

This information is furnished without warranty, express or implied. This information is believed to be accurate to the best knowledge of The information in this MSDS relates only to the specific material designated herein. MISH assumes no legal responsibility for use of or reliance upon the information in this MSDS.